ROTARY MULCHER





SHAKTIMAN Rotary Mulcher is robust and reliable implement for mulching of vineyards, orchard pruned materials, grass, bushes, crop residues like sugarcane trash, wheat & paddy straw, maize stalk etc. Mulcher shreds the crop residues/grass into small pieces and spread on the field. Which serves as bio mulch and decomposes gradually, improving overall organic structure of soil. Built with fine quality component like all other SHAKTIMAN products, this mulcher yield higher productivity and in turn ensures greater satisfaction.

Advantages

- It is highly compatible to shred vineyards & orchard pruned materials, grass, bushes, crop residues like sugarcane trash, wheat & paddy straw, maize stalk as thick as 5 cm in diameter.
- Bio mulch serves dual proposes Benefits of mulching and improve soil fertility after decomposition
- Effectively shaves sugarcane stubble, results in harmonious growth & higher yield.



ROTARY MULCHER

Rotary Mulcher - Technical Specifications

Model	HP Kw		+ "Y"Blade Straight Blade (Qty)		Hammer (Qty)	Weight(Kg / lbs)	Over All Dimension (mm) L W I		nsions H
SRM 1.6M	45-80	33.55-59.65	32	16	16	523 / 1153	2140	1150	1110
SRM 1.8M	45-80	33.55-59.65	36	18	18	558 / 1230	3990	1150	1110
SRM 2.0M	45-80	33.55-59.65	40	20	20	591 / 1303	5840	1150	1110
SRM 2.2M	45-80	33.55-59.65	44	22	22	650 / 1433	7690	1150	1110

Drive Transmission Type: Belt Drive

Tractor Power Transmission Shaft Type: Over Running Clutch Type P.T.O

The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice. "Weight is including rear leveller & excluding PTO and rear tyre"

Rotary Mulcher - Hydraulic: Technical Specifications

Model	HP (Kw	"Y"Blade	+ Straight Blade (Qty)	Hammer (Qty)	Working Width	(mm / inch)	Adjustable (mm / inch)	Weight (Kg / lbs)	Over A	All Dimens (mm) W	asions H
SRM 1.6M	45-80	33.55-59.65	32	16	16	1650 / 65	680-970/300-1350	(26.77-38.19 / 11.81-53.15)	631 / 1390	1825	1160	1200
SRM 1.8M	45-80	33.55-59.65	36	18	18	1840 / 72.4	950-890/570-1260	(37.40-35.04 / 22.44-49.61)	676 / 1489	2025	1160	1200
SRM 2.0M	45-80	33.55-59.65	40	20	20	2020 / 79.5	950-1070/570-1450	(37.40-42.13/22.44-57.09)	713 / 1572	2225	1160	1200
SRM 2.2M	45-80	33.55-59.65	44	22	22	2210 / 87	1180-1060/800-144	40 (46.46-41.73/31.50-56.69)	759 / 1673	2445	1160	1200

Features



Rear Roller with height adjustment ensures uniform and compact mulching layer.



- Free moving Gear Box Ensure safety of Tractor at the time of sudden switch
- Electronically Balance rotor Ensure vibration free working of mulcher to minimize maintenance.



- 3 point linkage suitable for cat I & II
- Standard input RPM 540
 - Side Drive Belts Side Drive Transmission: 4nos. BX 54 belts

The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice.

*Accessories shown are not part of standard equipment.

Drive Transmission Type: Belt Drive Tractor Power Transmission Shaft Type:

The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice. "Weight is including rear leveller & excluding PTO and rear tyre "



Optional:

- Hammer type blades for hard crop residues like coconut frond, orchard branches etc.
- Depth Wheels To crush Banana stem



Hydraulic side shift mechanism -To facilitate closer working to orchards.









Tirth Agro Technology Pvt. Ltd.

"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot. State: Gujarat - INDIA, Pin - 360 311. Phone: + 91 (2827) 661637 (30 Lines), + 91 (2827) 270 537, Fax: + 91 (2827) 270 457 Email: info@shaktimanagro.com, Web: www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435

Correspondence: Nr. Hotel Krishna Park, N.H. 27, Vavdi, Rajkot - 360 004, Gujarat, India.



