



Rotary Tiller

SHAKTIMAN offers a wide range of Rotary tillers to customer to select the right product for their tillage need depended on the type of soil, type of crop and depth required.

- It is available in sizes from 0.9 to 3 meters working width. Choices are also available for single speed, multi speed, chain drive, gear drive and types of blades as per requirement
- It's specially designed blade rotor reduces load on tractor as well as diesel consumption and avoids tyre slippage
- Strong and sturdy design made for hassle free performance and better durability
- In-house manufactured Boron steel blades provides long lasting performance

Mini Series Rotary Tiller

MODEL	SRT - 0.8	SRT - 1.0	SRT - 1.2
Overall Length (mm)	1023	1206	1389
Overall Width (mm)	670		
Overall Height (mm)	949		
Tilling Width (mm / inch)	887 / 35	1070 / 42.1	1253 / 49.3
Tractor Power	HP	12-22	15-25
	Kw	9-17	11-19
	19-26		
3-Point Hitch Type	Cat - I		
Frame Off-set (mm / inch)	36 / 1.4	7 / 0.3	0
Number of Tines (L-70x6)	16	20	24
Number of Tines (J-40x7)	30	36	42
Standard Tine Construction	Curved / Square		
Transmission Type	Gear / Chain		
Max. Working Depth (mm / inch)	152 / 6		
Rotor Tube Diameter (mm / inch)	73 / 2.9		
Rotor Swing Diameter (mm / inch)	412 / 16.2		
Driveline Safety Device	Shear Bolt		
Weight (Kg / lbs)	167 / 369	177 / 391	201 / 444

The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice.

"Weight is including safety guards & excluding PTO"

*Accessories shown are not part of standard equipment.



Optional:

- Chain Drive/Gear Drive
- Blades: L type / J type

Rotor RPM chart

Series	Input RPM	Gear Box Type	DRIVE	Rotor RPM
Mini	540	SS	CD	244
			GD	215