

U SERIES ROTARY TILLER



UL36-UL48-UL60



UM53-UM72



UH60-UH72-UH84



World's Largest Manufacturer of Rotary Tiller

U SERIES ROTARY TILLER

Model		UL36	UL42	UL48	UL60	UM53	UM60	UM72	UH60	UH72	UH84
Overall Length	mm	1035	1194	1340	1645	1500	1775	1970	1834	2063	2292
Overall Width	mm	805	805	805	805	940	940	940	1055	1055	1055
Overall Height	mm	600	600	600	600	720	720	720	795	795	795
Tilling Width	inch	36	42	48	60	53	65	72	65	72	84
	mm	915	1067	1220	1525	1350	1651	1829	1681	1910	2139
Tractor Power	HP	15-25	20-30	20-35	25-40	25-40	30-45	35-50	40-55	45-60	50-65
	Kw	11-19	15-22	15-26	19-30	19-30	22-34	26-37	30-41	34-45	37-48
3-Point Hitch Type		CAT I, Compat. Quick Hitch I cat. ASAE	CAT I, Compat. Quick Hitch I cat. ASAE	CAT I, Compat. Quick Hitch I cat. ASAE	CAT I, Compat. Quick Hitch I cat. ASAE	CAT I, Compat. Quick Hitch I cat. ASAE	CAT I, Compat. Quick Hitch I cat. ASAE	CAT I, Compat. Quick Hitch I cat. ASAE	CAT I & II	CAT I & II	CAT I & II
Frame Off-set	inch	-	-	4 or nil	-	-	-	-	-	-	-
No. of Tines per Rotor		24	30	36	42	42	48	54	42	48	54
PTO Input Speed	RPM	540	540	540	540	540	540	540	540	540	540
Rotor Shaft Speed	RPM@540	245	245	245	245	241	241	241	241	241	241
Standard Tine Construction		curved	curved	curved	curved	curved	curved	curved	curved	curved	curved
Transmission Type		gear	gear	gear	gear	gear	gear	gear	gear	gear	gear
Max. Working Depth	mm / inch	165 / 6.5	165 / 6.5	165 / 6.5	165 / 6.5	180 / 7	180 / 7	180 / 7	190 / 7.5	190 / 7.5	190 / 7.5
Rotor Tube Diameter	mm / inch	70 / 2.8	70 / 2.8	70 / 2.8	70 / 2.8	76 / 3	76 / 3	76 / 3	89 / 3.5	89 / 3.5	89 / 3.5
Rotor Swing Diameter	mm / inch	375 / 14.8	375 / 14.8	375 / 14.8	375 / 14.8	434 / 17.1	434 / 17.1	434 / 17.1	480 / 18.9	480 / 18.9	480 / 18.9
Driveline Safety Device		slip clutch	slip clutch	slip clutch	slip clutch	slip clutch	slip clutch	slip clutch	slip clutch	slip clutch	slip clutch
Weight (*)	lbs	337	368	399	441	564	627	683	860	926	990
	kg	153	167	181	200	256	285	310	390	420	450

Advantages:

- Hard-packed soil and dirt is turned up to leave an excellent seedbed for grass, gardens, food plots and lawn planting
- All models are built for years of dependable service
- Suitable for any tilling operation

Optional:

- Three point hitch plates for UL Series
- UL48 Center mounting available

UL-1.2(UL 48) center mounted model available as per req.

The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice.

"Weight is including safety guards & excluding PTO"

*Accessories shown are not part of standard equipment.



Tirth Agro Technology Pvt. Ltd.

"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot.
State: Gujarat - INDIA, Pin - 360 311. Phone: + 91 (2827) 661637 (30 Lines), + 91 (2827) 270 537, Fax: + 91 (2827) 270 457
Email: info@shaktimanagro.com, Web: www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435

Correspondence : Nr. Hotel Krishna Park, N.H. 27, Vavdi, Rajkot - 360 004, Gujarat, India.

Scan to Visit Website



World's Largest Manufacturer of Rotary Tiller