

VIKTOR ROTARY TILLER



SHAKTIMAN offers a wide range of Rotary tillers to customer to select the right product for their tillage need depended on the type of soil, type of crop and depth required.

- It is available in sizes from 1.5 to 2.25 meters working width. Choices are also available for single speed, multi speed and types of blades as per requirement
- It's specially designed blade rotor reduces load on tractor as well as diesel consumption and avoids tyre slippage
- Strong and sturdy design made for hassle free performance and better durability
- In-house manufactured Boron steel blades provides long lasting performance



VIKTOR ROTARY TILLER

MODEL	SRT - 150	SRT - 175	SRT - 200	SRT - 225	
Overall Length (mm)	1705	1945	2185	2425	
Overall Width (mm)	1085				
Overall Height (mm)	1263				
Tilling Width (mm / inch)	1540 / 60.6	1780 / 70.1	2020 / 79.5	2260 / 89	
Tractor Power	HP	50-65	60-75	70-85	80-95
	Kw	37-48	45-56	52-63	60-71
3-Point Hitch Type	Cat - II				
Frame Off-set (mm / inch)	5 / 0.20	0	0	4 / 0.17	
No. of Tines (L/C-90x8)	36	42	48	54	
Standard Tine Construction	Curved / Square				
Transmission Type	Gear				
Max. Working Depth (mm / inch)	225 / 9				
Rotor Tube Diameter (mm / inch)	89 / 3.5				
Rotor Swing Diameter (mm / inch)	521 / 20.50				
Driveline Safety Device	Slip Clutch / Shear Bolt				
Weight (Kg / lbs)	580 / 1280	621 / 1370	664 / 1464	706 / 1557	

The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice.

"Weight is including safety guards & excluding PTO"



Tirth Agro Technology Pvt. Ltd.

"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot.
 State: Gujarat - INDIA, Pin - 360 311. Phone: + 91 (2827) 661637 (30 Lines), + 91 (2827) 270 537, Fax: + 91 (2827) 270 457
 Email: info@shaktimanagro.com, Web: www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435

Correspondence : Nr. Hotel Krishna Park, N.H. 27, Vavdi, Rajkot - 360 004, Gujarat, India.

Advantages:

- Multi-purpose - Suitable for both dryland & wetland cultivation
- Suitable for medium to heavy soils
- Available in 4 ft, 5 ft, 5.5 ft, 6 ft, 7 ft and 8 ft width

Optional:

- Gear Box: Single Speed/Multi speed
- Blades: C type/ L type
- Drive Shaft: Shear Bolt/ Slip Clutch

Rotor RPM Chart

Series	Input RPM	Gear Box	Spur Gear 1	Spur Gear 2	Rotor Speed
Viktor (GD)	540	SS	-	-	226
		MS	16	19	191
			17	18	214
		18	17	240	
	1000	MS	13	22	248

Standard Gear Pair 17-18

Scan to Visit Website

